

Amendments to the Claims:RECEIVED
CENTRAL FAX CENTER

DEC 22 2006

1 - 19. (canceled)

20. (currently amended) A method for temporary temporarily marking an object (O) at a site in a process chain, the method comprising ~~the~~ a step of applying a coating composition (3) to the object (O) by a marking device, ~~the~~ said coating composition (3) comprising a short-lived radioactive isotope, wherein said short-lived radioactive isotope has a half-life time in the range of between a minute and a day and is generated ~~in-situ~~ at said site from a longer-lived radioactive precursor isotope and added to said coating composition (3) in said marking device.

21. (canceled)

22. (previously presented) Method according to claim 20, wherein said short-lived radioactive isotope is a gamma-radiation emitter or a $\beta(+)$ -emitter.

23. (previously presented) Method according to claim 20, wherein said short-lived radioactive isotope is selected from the group consisting of 99m-Tc, 60m-Co, 90m-Y, 103m-Rh, 106m-Rh, 137m-Ba, 144m-Pr, 144-Pr, 212-Pb, and 211-Pb.

24. (previously presented) Method according to claim 20, wherein said coating composition (3) is applied to said object (O) by ink-jet printing or by a spraying operation.

25. (previously presented) Method according to claim 24, wherein said ink-jet printing or spraying is of the drop-on-demand type.

26. (previously presented) Method according to claim 20, wherein said coating composition (3) contains at least one binder.
27. (previously presented) Method according to claim 20, wherein the application of said coating composition (3) is performed upon receipt of a particular signal by said marking device.
28. (previously presented) Method according to claim 27, wherein said particular signal is an electric signal.
29. (currently amended) Device suitable for ~~temporary~~ temporarily marking an object (O) in a process chain, said device comprising a short-lived radionuclide generator (1), a first reservoir (2) of a printing liquid, a splitting valve (5), a radiation monitor (6), a control unit (7) and a printing or marking head (8).
30. (previously presented) Device according to claim 29, wherein said radionuclide generator (1) generates a gamma-emitting or $\beta(+)$ -emitting radioactive isotope, said radioactive isotope having a half-life time in the range of between a minute and a day.
31. (previously presented) Device according to claim 30, wherein said radionuclide generator (1) generates a gamma-emitting short-lived radioactive isotope, which is selected from the group consisting of ^{99m}Tc , ^{60m}Co , ^{90m}Y , ^{103m}Rh , ^{106m}Rh , ^{137m}Ba , ^{144m}Pr , ^{144}Pr , ^{212}Pb , and ^{211}Pb .
32. (previously presented) Device according to claim 29, wherein said printing or marking head (8) is an ink-jet printing head.
33. (previously presented) Device according to claim 32, wherein said ink-jet printing head is a drop-on-demand ink-jet printing head.

34. (previously presented) Device according to claim 29, wherein said device comprises further a second reservoir (11) which contains printing liquid, and a dosing pump (13), the printing liquid being free of radioactive isotopes.

35. (currently amended) A system for temporary temporarily marking an object (O) in a process chain, said system comprising

a) at least one device for temporary temporarily marking an object (O); and

b) at least one detecting device for detecting the presence of the temporary marking on an object (O),

wherein said device for applying the temporary marking comprises a short-lived radionuclide generator (1), a first reservoir (2) of a printing liquid, a splitting valve (5), a radiation monitor (6), a control unit (7) and a printing or marking head (8),

wherein said device is activated upon receipt of a signal, and

wherein said detecting device is capable of detecting gamma-radiation, and producing a signal, upon detection of said temporary marking.

36. (previously presented) The system according to claim 35, wherein said signal activating said device is an electric signal.

37. (previously presented) The system according to claim 35, wherein said signal produced by said detecting device is an electric signal.

38. (currently amended) A method for temporary temporarily marking and identifying an object (O), the method comprising the steps of

[[-]] applying a coating composition (3) to the object (O), by a marking device, wherein said coating composition (3) comprises a short-lived radioactive isotope having a half-life time in the range of between a minute and a day; and

[[-]] identifying said temporary marking by detecting gamma-radiation emitted by the short-lived radioactive isotope;

wherein said short-lived radioactive isotope is generated in situ from a longer-lived radioactive precursor isotope and added to said coating composition (3) in said marking device.